



NMGC

No melt grease

will NOT melt or drip even at >+260°C

PROPERTIES:

Thickener: **Lithium complex**
Base fluid: **Mineral oil/Polymer**
Colour: **Orange**, NLGI grade ASTM D 217 mod: 2
Temperature Range: **-20°C - +180°C**
Penetration 60 strokes ISO 2137: **265 - 295**
Dropping point IP 396: **>260°C**
Base oil visc. at 40°C ASTM D 7152: 800 mm²/s
Base oil visc. at 100°C ASTM D7152 44 mm²/s
Water resistance at 90°C DIN 51807:1: **1**
Water wash out at 79°C ISO 11009: **<10%**
Emcor salt water ISO 11007: **<2 - 2**
Flow pressure at -20°C DIN 51805 mod: **<1400 mbar**
4-ball weld load DIN 51350:4: **3200 N**
SKF R2F B at 140°C - SKF: **Pass**
Density IP 530: 900 kg/m³
Non-lead based EP (extreme pressure) agent.



**NMG refuses to melt
- even in naked flames**

OPERATIONAL PERFORMANCE

- BiRAL NMG will not melt, drip nor run even if ignited.
- BiRAL NMG withstands extremely heavy loads.
- BiRAL NMG is highly adhesive and water repellent.
- BiRAL NMG Protects from rust, corrosion and chemical attack.
- BiRAL NMG Provides lubrication over extended periods

GENERAL AREAS OF APPLICATION:

BiRAL NMG is excellent wherever lubricating problems occur due to high temperatures, heavy loads and aggressive environments/conditions. Examples are conveyors, chains and moving parts for stove enamelling, sintering presses, ovens (radiant heat or IR) autoclaves, drying plant, paint booths, bottling plants, packaging and carton making machines, bearings and equipment frequently subjected to extremes of heat, steam, seawater and aggressive chemical attack.

BiRAL NMG is based on a mixture of mineral oil and polymer, containing antioxidants, corrosion inhibitors and EP/AW additives. The lithium complex soap blended in this mixture, makes the product suitable for applications at elevated temperatures, heavily loaded bearings and wet and corrosive environments. This structure gives NMG a high degree of mechanical stability



BiRAL Lubricants Norway A/S

P.o.Box 35 - N-1300 Sandvika - Norway

Tel: (47) 6756.5000 - Fax: (47) 6756.5161 - E-mail: Hq@biral.no - www.biralube.com